Printing date 22.01.2019

Version number 5

Revision: 22.01.2019

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
- · Trade name: Castdon Monomer
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture
- Dental denture resin for the production of total and partial dentures
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: Dreve Dentamid GmbH Max-Planck-Straße 31 59423 Unna / Germany Tel.: ++49 2303 /8807-0 Fax.: ++49 2303 / 8807-55
- · Further information obtainable from: **Department Research & Development** Fax: ++49 2303 / 8807-562 Email: sicherheitsdatenblatt@dreve.de
- · 1.4 Emergency telephone number: Tel.: ++ 49 211 / 797-3350 Plant Fire Department Henkel

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 2 H225 Highly flammable liquid and vapour.

GHS07

Skin Irrit. 2 H315 Causes skin irritation. Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation.

· 2.2 Label elements

- · Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms



· Signal word Danger

· Hazard-determining components of labelling: methyl methacrylate 1,4 Butanediol dimethacrylate

(Contd. on page 2)

GB



Printing date 22.01.2019

· Hazard statements

Version number 5

Revision: 22.01.2019

Trade name: Castdon Monomer

(Contd. of page 1)

H225 Highly flammable liquid and vapour.				
H315 Causes skin irritation.				
H317 May cause an allergic skin reaction.				
H335 May cause respiratory irritation.				
· Precautionary statements				
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.				
P241 Use explosion-proof electrical/ventilating/lighting equipment.				
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.				
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.				
P405 Store locked up.				
P501 Dispose of contents/container in accordance with local/regional/national/ international regulations.				
· 2.3 Other hazards				
. Results of PRT and vPvR assessment				

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

• **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• **Description:** Liquid based on methacrylate acid ester, containing an activator

· Dangerous components:			
CAS: 80-62-6	methyl methacrylate	50-100%	
EINECS: 201-297-1	🚸 Flam. Liq. 2, H225; 🚸 Skin Irrit. 2, H315; Skin Sens. 1, H317;		
	STOT SE 3, H335		
	1,4 Butanediol dimethacrylate	2.5-10%	
EINECS: 212-218-1	♦ Skin Sens. 1, H317		
• Additional information: For the wording of the listed hazard phrases refer to section 16.			

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

• After skin contact: Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing:

Do not induce vomiting.

Call a doctor immediately.

• **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 3)

GB -



Printing date 22.01.2019

Version number 5

Revision: 22.01.2019

Trade name: Castdon Monomer

(Contd. of page 2) • 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fire with alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- Additional information
- Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Avoid contact with skin and eyes. Ensure adequate ventilation Keep away from ignition sources. Wear protective equipment. Keep unprotected persons away.
6.2 Environmental precautions: Do not allow to penetrate the ground/soil. Prevent seepage into sewage system, workpits and cellars. Do not allow to enter sewers/ surface or ground water.
6.3 Methods and material for containment and cleaning up: Send for recovery or disposal in suitable receptacles. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Avoid contact with skin and eyes.
 Ensure good ventilation/exhaustion at the workplace.
 Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Protect from heat and direct sunlight.

(Contd. on page 4)

ЗB



Printing date 22.01.2019

Version number 5

Revision: 22.01.2019

(Contd. of page 3)

Trade name: Castdon Monomer

Store between 10 °C and 25°C at a well ventilated place. Store in a cool location.

- Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions:
- Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

80-62-6 methyl methacrylate

WEL Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.

Respiratory protection: Not necessary if room is well-ventilated. Do not inhale fumes. Protection of hando:

Protection of hands:



Protective gloves

Protective gloves should be changed regularly, especially after intensive contact with the product. For every workplace a suitable type of protective gloves must be selected.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

Butyl rubber (0,7 mm) EN 374

As there are many different conditions in every day work these indications can only serve as an aid to orientation for the selection of suitable gloves for the handling of chemical products. By no means they can replace qualifying examinations by the end-user.

These recommendations only apply to the product mentioned in the safety data sheet. When mixing with other substances or under conditions deviant from norm EN 374 a manufacturer of CE-approved gloves should be referred to.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

GB



Printing date 22.01.2019

Version number 5

Revision: 22.01.2019

Trade name: Castdon Monomer

(Contd. of page 4)

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

\cdot 9.1 Information on basic physical and o	chemical properties
· General Information	
· Appearance: Form:	Fluid
Colour:	Fluid Colourless
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/freezing point:	-48 °C
Initial boiling point and boiling range	: 101 °C
· Flash point:	10 °C
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	430 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	2.1 Vol %
Upper:	12.5 Vol %
· Oxidising properties	Not determined
· Vapour pressure at 20 °C:	47 hPa
· Density at 20 °C:	0.95 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
	(Contd. on page 6

– GB

Printing date 22.01.2019

Version number 5

Revision: 22.01.2019

Trade name: Castdon Monomer

(Contd. of page 5)

· Viscosity:

Dynamic:

Kinematic:

· 9.2 Other information

Not determined. Not determined. No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No dangerous reactions if used according to specifications.
- · 10.2 Chemical stability Stable if used according to specifications.
- Thermal decomposition / conditions to be avoided: Protect from heat and direct sunlight.

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions Danger of polymerisation.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials:

Reacts with peroxides and other radical forming substances.

Reacts with reducing agents.

Reacts with heavy metals.

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

• 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

Methylmethacrylate: LD-50 oral >5000 mg/kg rat (Lit.)

LD-50 inhalativ 7093 ppm/4h rat (Lit.)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

- Serious eye damage/irritation Low irritant effect
- · Respiratory or skin sensitisation
- May cause an allergic skin reaction.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure
- May cause respiratory irritation.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- \cdot Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

 Aquatic toxicity: Fish Toxicity (MMA): LC-50 > 79 mg/l OECD 203 NOEC: 40 mg/l ISO 7346 Exposure: 96 h EEC84 Spezies: 449 V, C1 Oncorhynchus mykiss



Printing date 22.01.2019

Version number 5

Revision: 22.01.2019

Trade name: Castdon Monomer

(Contd. of page 6) Bacterial Toxicity: ECO: 100 mg/l Spezies of cells: Pseudomonas putida · 12.2 Persistence and degradability No further relevant information available. · Behaviour in environmental systems: · Components: Methylmethacrylat: Biodegradability: 30,7 % Test Duration: 28 d Method: OECD 301 C Scoring: Not ready degradability · 12.3 Bioaccumulative potential No further relevant information available. · 12.4 Mobility in soil No further relevant information available. · Additional ecological information: · General notes: Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. · 12.5 Results of PBT and vPvB assessment • **PBT:** Not applicable. · vPvB: Not applicable. · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

• Waste disposal key: 070104

· European waste catalogue	
HP 3	Flammable
HP 4	Irritant - skin irritation and eye damage
HP 5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP 13	Sensitising

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information		
· 14.1 UN-Number · ADR, IMDG, IATA	UN1247	
· 14.2 UN proper shipping name		
· ADR	1247 METHYLMETHACRYLAT, MONOMER, STABILISIERT, Lösung	
· IMDG, IATA	METHYL METHACRYLATE MONOMER, STABILIZED, Solution	
	(Contd. on page 8)	

- GB -

Printing date 22.01.2019

Trade name: Castdon Monomer

Safety data sheet according to 1907/2006/EC, Article 31



Version number 5

Revision: 22.01.2019

(Contd. of page 7) · 14.3 Transport hazard class(es) · ADR, IMDG, IATA · Class 3 Flammable liquids. · Label 3 · 14.4 Packing group · ADR, IMDG, IATA Ш · 14.5 Environmental hazards: · Marine pollutant: No · 14.6 Special precautions for user Warning: Flammable liquids. Danger code (Kemler): 339 · EMS Number: F-E,S-D Stowage Category В · Stowage Code SW2 Clear of living quarters. · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. · Transport/Additional information: · ADR · Limited quantities (LQ) 1L · Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml · Transport category 2 · Tunnel restriction code D/E · IMDG · Limited quantities (LQ) 1L · Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml · UN "Model Regulation": UN 1247 METHYL METHACRYLATE MONOMER, STABILIZED, 3, II

SECTION 15: Regulatory information

 \cdot 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

(Contd. on page 9)

⁻ GB -



Printing date 22.01.2019

Version number 5

Revision: 22.01.2019

Trade name: Castdon Monomer

· REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

(Contd. of page 8)

- · National regulations:
- · Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour. H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

- · Department issuing SDS: Department Research & Development
- Contact: Dr. Thomas Veit, Lothar Sutor, Susanne Langesberg

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA) ICAO: International Civil Aviation Organisation ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO) ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids - Category 2 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Skin Sens. 1: Skin sensitisation - Category 1 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3