

Page 1/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.08.2022

Version number 4 (replaces version 3)

Revision: 03.08.2022

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
 - · Trade name: Palavit G Liquid
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
 - · Application of the substance / the mixture Manufacture of dental prothesis
- · 1.3 Details of the supplier of the safety data sheet
 - Manufacturer/Supplier:

Kulzer GmbH

Leipziger Straße 2, 63450 Hanau (Germany)

Tel.: +49 (0)800 4372522

- · Informing department: E-Mail: msds@kulzer-dental.com
- · 1.4 Emergency telephone number: Emergency CONTACT (24-Hour-Number): +49 (0)6132-84463

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
 - Classification according to Regulation (EC) No 1272/2008

Flam. Lig. 2 H225 Highly flammable liquid and vapour.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- · 2.2 Label elements
 - Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

methyl methacrylate

N,N-dimethyl-p-toluidine

· Hazard statements

H225 Highly flammable liquid and vapour.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P260 Do not breathe mist/vapours/spray. P280 Wear protective gloves / eye protection. P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P312 IF INHALED: Call a doctor if you feel unwell.

· 2.3 Other hazards -

· Results of PBT and vPvB assessment

PBT: Not applicable.

(Contd. on page 2)



Page 2/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.08.2022 Version number 4 (replaces version 3) Revision: 03.08.2022

Trade name: Palavit G Liquid

· vPvB: Not applicable.

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
 - · Description: -

· Dangerous components:		
CAS: 80-62-6	methyl methacrylate	>90%
EINECS: 201-297-1	Flam. Liq. 2, H225 Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	
CAS: 99-97-8	N,N-dimethyl-p-toluidine	≥2.5-<5%
EINECS: 202-805-4	Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2,	
Reg.nr.: 01-2119956633-31-xxxx	H330	
	STOT RE 2, H373	
	Aquatic Chronic 3, H412	

[·] Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
 - General information

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation Supply fresh air; consult doctor in case of symptoms.
- · After skin contact

Instantly wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact

Rinse opened eye for several minutes under running water. Then consult doctor.

After swallowing

Rinse out mouth and then drink plenty of water.

In case of persistent symptoms consult doctor.

- · Information for doctor Product based on methacrylates
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
 - · Suitable extinguishing agents CO2, sand, extinguishing powder. Do not use water.
 - · For safety reasons unsuitable extinguishing agents Water.
- · 5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters
 - Protective equipment:

Wear self-contained breathing apparatus.

Put on breathing apparatus.

(Contd. on page 3)



Page 3/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.08.2022 Version number 4 (replaces version 3) Revision: 03.08.2022

Trade name: Palavit G Liquid

· Additional information -

(Contd. of page 2)

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Wear protective equipment. Keep unprotected persons away.

 6.2 Environmental precautions: Prevent material from reaching sewage system, holes and cellars.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (diatomite, universal binders, for small amounts tissues).

Dispose of contaminated material as waste according to item 13.

· 6.4 Reference to other sections

No dangerous materials are released.

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep containers tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
 - Storage
 - Requirements to be met by storerooms and containers: Store in cool location.
 - Information about storage in one common storage facility: Not required.
 - Further information about storage conditions:
 - Store in cool, dry conditions in well sealed containers.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical values that require monitoring at the workplace:

80-62-6 methyl methacrylate

WEL (Great Britain) Short-term value: 416 mg/m³, 100 ppm

Long-term value: 208 mg/m³, 50 ppm

Short-term value: 100 ppm IOELV (European Union)

Long-term value: 50 ppm

· DNELs

80-62-6 methyl methacrylate

Oral general population, long term, systemic 8.2 mg/Kg (not defined) Dermal worker industrial, long term, systemic 13.67 mg/Kg/d (not defined) general population, long term, systemic 8.2 mg/Kg/d (not defined)

(Contd. on page 4)



Page 4/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.08.2022 Version number 4 (replaces version 3) Revision: 03.08.2022

Trade name: Palavit G Liquid

				(Contd. of page 3)
Inhalative	worker industrial, acute, loc	cal	416 mg/m3 (not defined)	, , ,
	worker industrial, long term	n, systemic	348.4 mg/m3 (not defined)	
	worker industrial, long term	n, local	208 mg/m3 (not defined)	
	general population, acute,	local	208 mg/m3 (not defined)	
	general population, long te	erm, systemic	74.3 mg/m3 (not defined)	
· PNI	ECs			
80-62-6 m	ethyl methacrylate			
freshwater	hwater 0.94 mg/l (not defined)			

freshwater 0.94 mg/l (not defined)
marine water 0.094 mg/l (not defined)
sewage treatment plant 10 mg/l (not defined)
sediment, dry weight, freshwater sediment, dry weight, marine water soil, dry weight 1.48 mg/Kg (not defined)

· 8.2 Exposure controls

- Appropriate engineering controls No further data; see item 7.
- Individual protection measures, such as personal protective equipment
 - General protective and hygienic measures

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

· Breathing equipment:

Not neccessary with efficient local exhaust. If exposition to vapours is possible, use breathing protective mask (filter A).

· Hand protection

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

If skin contact cannot be avoided, protective gloves are recommended to avoid possible sensitization.

Solvent resistant gloves

Check protective gloves prior to each use for their proper condition.

recommended

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 30 minutes (Permeation according to EN 16523-1:2015: Level 2).

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Butyl rubber, BR

Nitrile rubber, NBR

Eye/face protection Tightly sealed safety glasses.

(Contd. on page 5)

[·] Additional information: The lists that were valid during the compilation were used as basis.



Page 5/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.08.2022 Version number 4 (replaces version 3) Revision: 03.08.2022

Trade name: Palavit G Liquid

· Body protection: Light weight protective clothing

(Contd. of page 4)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

General Information

· Physical state Fluid · Colour: Colourless · Smell: Characteristic Odour threshold: Not determined.

-48 °C

· Melting point/freezing point: · Boiling point or initial boiling point and

100 °C boiling range

· Flammability Not applicable.

· Lower and upper explosion limit

2.1 Vol % Lower: · Upper: 12.5 Vol % 10 °C · Flash point: 430 °C Ignition temperature:

· Decomposition temperature: Not determined.

SADT

pН Mixture is non-soluble (in water).

Viscosity:

· Kinematic viscosity Not determined. dynamic: Not determined.

Solubility

Not miscible or difficult to mix Water:

· Partition coefficient n-octanol/water (log

value) at 20 °C 1.38 log POW · Steam pressure at 20 °C: 47 hPa

Density and/or relative density

Density at 20 °C 0.94 g/cm³ Relative density Not determined. Not determined. · Vapour density

· 9.2 Other information No further relevant information available.

Appearance:

Form: Fluid

· Important information on protection of health and environment, and on safety.

· Self-inflammability: Product is not selfigniting.

· Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures is possible.

Change in condition

Evaporation rate Not determined.

· Information with regard to physical hazard

classes

Void **Explosives** Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void

· Flammable liquids Highly flammable liquid and vapour.

(Contd. on page 6)



Page 6/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.08.2022 Version number 4 (replaces version 3) Revision: 03.08.2022

Trade name: Palavit G Liquid

		(Contd. of page 5)
· Flammable solids	Void	
· Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
· Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
· Oxidising liquids	Void	
· Oxidising solids	Void	
Organic peroxides	Void	
· Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
 - · Conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions Exothermic polymerisation
- · 10.4 Conditions to avoid Heat, flames and sparks.
- · 10.5 Incompatible materials:

Reacts with reducing agents

Reacts with heavy metals

Reacts with peroxides and other radical forming substances

- 10.6 Hazardous decomposition products: None
 - Additional information: -

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 · Acute toxicity

Harmful if inhaled.

· LD/	· LD/LC50 values that are relevant for classification:		
80-62-6 m	80-62-6 methyl methacrylate		
Oral	Oral LD50 ~7,900 mg/kg (rat)		
Dermal	LD50	>5,000 mg/kg (guinea pig) (OECD 402)	
Inhalative	LC50/4 h	29.8 mg/l (rat)	
99-97-8 N	99-97-8 N,N-dimethyl-p-toluidine		
Oral	LD50	139 mg/kg (rat)	

· Skin corrosion/irritation

Causes skin irritation.

- · Serious eye damage/irritation No data available.
- · Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause respiratory irritation.

- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 7)



Page 7/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.08.2022 Version number 4 (replaces version 3) Revision: 03.08.2022

Trade name: Palavit G Liquid

(Contd. of page 6)

· 11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

80-62-6 metl	hyl metha	acrylate
EC50/21d	40 ma/l	(danhni

· Aquatic toxicity:

EC50/21d 49 mg/L (daphnia) (OECD 211)

EC50/48h 69 mg/l (daphnia) (EPA OTS 797.1300)

NOEC / 21d | 37 mg/l (daphnia) (OECD 211)

ErC50 / 72 h >110 mg/l (algae) (OECD 201)

NOEC / 72h | 110 mg/l (algae) (OECD 201)

NOEC / 48h | 48 mg/l (daphnia) (EPA OTS 797.1300)

EbC50 / 72h >110 mg/l (algae) (OECD 201) NOEC/ 35d 9.4 mg/L (fish) (OECD 210) LC50/ 35d 33.7 mg/L (fish) (OECD 210)

99-97-8 N,N-dimethyl-p-toluidine

LC50/96h 100 mg/l (fish)

· 12.2 Persistence and degradability

80-62-6 methyl methacrylate

Biodegradation 94 % /14d (not defined) (OECD 301C)

- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
 - · PBT: Not applicable.
 - · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- 12.7 Other adverse effects
 - · Additional ecological information:
 - · General notes:

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

· Recommendation

Disposal must be made according to official regulations.

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:
 - · Recommendation:

Disposal must be made according to official regulations.

(Contd. on page 8)



Page 8/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.08.2022 Version number 4 (replaces version 3)

Revision: 03.08.2022

Trade name: Palavit G Liquid

Non contaminated packagings can be used for recycling.

(Contd. of page 7)

14.1 UN number or ID number · ADR, IMDG, IATA	UN1247
14.2 UN proper shipping name ADR	1247 METHYL METHACRYLATE MONOME STABILIZED solution
· IMDG, IATA	METHYL METHACRYLATE MONOME STABILIZED solution
14.3 Transport hazard class(es)	
ADR	
· Class · Label	3 (F1) Flammable liquids. 3
· IMDG, IATA	
· Class · Label	3 Flammable liquids. 3
14.4 Packing group ADR, IMDG, IATA	II
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user Kemler Number:	Warning: Flammable liquids.
· Kemler Number: · EMS Number:	339 F-E,S-D
Stowage Category	г-с, <u>з-о</u> В
Stowage Code	SW2 Clear of living quarters.
14.7 Maritime transport in bulk according IMO instruments	i to Not applicable.
· Transport/Additional information:	-
ADR	
Limited quantities (LQ)	1L
Excepted quantities (ÉQ)	Code: E2 Maximum net quantity per inner packagir
	30 ml Maximum net quantity per outer packagir
Tono and a state of the second	500 ml
· Transport category	2



Page 9/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.08.2022 Version number 4 (replaces version 3) Revision: 03.08.2022

Trade name: Palavit G Liquid

(Contd. of page 8)

·IMDG

· Limited quantities (LQ)

· Tunnel restriction code

Excepted quantities (ÉQ)

1L Code: E2

Maximum net quantity per inner packaging:

D/E

Maximum net quantity per outer packaging:

500 ml

UN "Model Regulation":

UN 1247 METHYL METHACRYLATE MONOMER, STABILIZED SOLUTION, 3, II

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
 - Directive 2012/18/EU
 - Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
 - Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H330 Fatal if inhaled.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Abbreviations and acronyms:

ADDreviations and actorymis:

SADT: Self Accelerating Decomposition Temperature

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (ÚK REACH)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic

vPVB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Acute Tox. 3: Acute toxicity – Category 3 Acute Tox. 2: Acute toxicity – Category 2

Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2

Skin Sens. 1: Skin sensitisation - Category 1

(Contd. on page 10)



Page 10/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.08.2022

Version number 4 (replaces version 3)

Revision: 03.08.2022

Trade name: Palavit G Liquid

(Contd. of page 9)

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
* * Data compared to the previous version altered.

CE