

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### sili spray Adhesive

Print date: 26.10.2015

Product code: 10105\_1

Page 1 of 9

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

sili spray Adhesive

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Professional  
Wetting agent for use in dentistry.

### 1.3. Details of the supplier of the safety data sheet

Company name:	DETAX GmbH & Co. KG	
Street:	Carl-Zeiss-Strasse	
Place:	D-76275 Ettlingen	
Telephone:	+49 7243/510-0	Telefax: +49 7243/510-100
e-mail:	post@detax.de	
Internet:	www.detax.de	
Responsible Department:	Emergency number:	

+49 7243/510-0

This number is only obtainable during office hours (Monday - Thursday 8.00 a.m. - 5.00 p.m., Friday 8.00 a.m. - 4.00 p.m.)

### 1.4. Emergency telephone

#### number:

+49 7243/510-0

This number is only obtainable during office hours (Monday - Thursday 8.00 a.m. - 5.00 p.m., Friday 8.00 - 4.00 p.m.)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Hazard categories:  
Aerosol: Aerosol 1  
Serious eye damage/eye irritation: Eye Irrit. 2  
Specific target organ toxicity - single exposure: STOT SE 3  
Hazard Statements:  
Extremely flammable aerosol.  
Pressurised container: May burst if heated.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.

### 2.2. Label elements

#### Hazardous components which must be listed on the label

acetone; propan-2-one; propanone  
butanone; ethyl methyl ketone  
ethyl acetate

Signal word:

Danger

Pictograms:



#### Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### sili spray Adhesive

Print date: 26.10.2015

Product code: 10105\_1

Page 2 of 9

H336 May cause drowsiness or dizziness.

#### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

#### 2.3. Other hazards

No information available.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Chemical characterization

Solvant in propellant. (liquefied butane gas)

##### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
67-64-1	acetone; propan-2-one; propanone			15 - < 20 %
	200-662-2	606-001-00-8		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
78-93-3	butanone; ethyl methyl ketone			10 - < 15 %
	201-159-0	606-002-00-3	01-2119457290-43	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
141-78-6	ethyl acetate			1 - < 5 %
	205-500-4	607-022-00-5	01-2119475103-46	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			

Full text of H and EUH phrases: see section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### After inhalation

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

##### After contact with skin

Wash with plenty of water. Take off contaminated clothing and wash it before reuse.

##### After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

##### After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink plenty of water. Do not induce vomiting. If you feel unwell, seek medical advice.

#### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### sili spray Adhesive

Print date: 26.10.2015

Product code: 10105\_1

Page 3 of 9

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### **Suitable extinguishing media**

Carbon dioxide (CO<sub>2</sub>), Foam, Extinguishing powder.

#### **Unsuitable extinguishing media**

Water.

### 5.2. Special hazards arising from the substance or mixture

Flammable. Vapours can form explosive mixtures with air.

### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

#### **Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

### 6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

### 6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### **Advice on safe handling**

Do not pierce or burn, even after use. If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

#### **Advice on protection against fire and explosion**

Do not spray on naked flames or any incandescent material. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

### 7.2. Conditions for safe storage, including any incompatibilities

#### **Requirements for storage rooms and vessels**

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

#### **Advice on storage compatibility**

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

Do not store with flammable liquids, flammable solid substances or desensitised substances, spontaneously flammable substances, substances liberating flammable gases in contact with water, combustible liquids.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### sili spray Adhesive

Print date: 26.10.2015

Product code: 10105\_1

Page 4 of 9

#### Further information on storage conditions

Keep only in the original container in a cool, dry and well-ventilated place, away from foodstuffs.

#### 7.3. Specific end use(s)

Wetting spray for use in dental technology.  
For use by trained specialist staff.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
78-93-3	Butan-2-one (methyl ethyl ketone)	200	600		TWA (8 h)	WEL
		300	899		STEL (15 min)	WEL
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL
141-78-6	Ethyl acetate	200	-		TWA (8 h)	WEL
		400	-		STEL (15 min)	WEL

#### Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
78-93-3	Butan-2-one	butan-2-one	70 µmol/L	urine	Post shift

#### 8.2. Exposure controls

##### Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

##### Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

##### Eye/face protection

Suitable eye protection: goggles.

##### Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Suitable are gloves of the following material: Butyl caoutchouc (butyl rubber), FKM (fluoro rubber)

##### Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

##### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### sili spray Adhesive

Print date: 26.10.2015

Product code: 10105\_1

Page 5 of 9

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state: liquided gas with liquid part, compressed  
 Colour: colourless  
 Odour: like benzene

#### Test method

pH-Value: not determined

#### Changes in the physical state

Melting point: not determined  
 Initial boiling point and boiling range: not determined

Flash point: <-10 °C DIN 51755

#### Flammability

Solid: not applicable

Gas: not applicable

Lower explosion limits: 1,5 vol. %

Upper explosion limits: 8,5 vol. %

Ignition temperature: 365 °C DIN 51794

#### Auto-ignition temperature

Solid: not applicable

Gas: not applicable

Decomposition temperature: not determined

#### Oxidizing properties

Not oxidizing.

Vapour pressure: 9000 hPa  
 (at 70 °C)

Density (at 15 °C): 0,68 g/cm<sup>3</sup> DIN 51757

Water solubility: insoluble

#### Solubility in other solvents

not determined

Partition coefficient: not determined

Vapour density: not determined

Evaporation rate: not determined

### 9.2. Other information

Solid content: not determined

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Flammable, Ignition hazard.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

Reacts with : flammable, spontaneously flammable and combustible substances. Prevent any contact

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### sili spray Adhesive

Print date: 26.10.2015

Product code: 10105\_1

Page 6 of 9

of the product with strong oxidising agents, such as chlorine or concentrated oxygen.

#### 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Higher temperatures advance the formulation of explosive vapour-air mixtures, therefore don't expose the product to increased temperatures.

#### 10.5. Incompatible materials

No information available.

#### 10.6. Hazardous decomposition products

No known hazardous decomposition products.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name	Exposure routes	Method	Dose	Species	Source
67-64-1	acetone; propan-2-one; propanone	oral	LD50	5800 mg/kg	Rat	RTECS
		dermal	LD50	20000 mg/kg	Rabbit	IUCLID
		inhalative (4 h) vapour	LC50	76 mg/l	Rat	
78-93-3	butanone; ethyl methyl ketone	oral	LD50	>2000 mg/kg	Rat	
		dermal	LD50	>2000 mg/kg	Rabbit	
141-78-6	ethyl acetate	oral	LD50	>2000 mg/kg	Rat	
		dermal	LD50	>2000 mg/kg	Rabbit	

#### Irritation and corrosivity

Causes serious eye irritation.

#### Sensitising effects

Based on available data, the classification criteria are not met.

#### STOT-single exposure

May cause drowsiness or dizziness. (acetone; propan-2-one; propanone), (butanone; ethyl methyl ketone), (ethyl acetate)

#### Severe effects after repeated or prolonged exposure

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### Additional information on tests

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].

## SECTION 12: Ecological information

### 12.1. Toxicity

The product is not: Ecotoxic.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### sili spray Adhesive

Print date: 26.10.2015

Product code: 10105\_1

Page 7 of 9

CAS No	Chemical name					
	Aquatic toxicity	Method	Dose	[h]   [d]	Species	Source
67-64-1	acetone; propan-2-one; propanone					
	Acute fish toxicity	LC50	5540 mg/l	96 h	Onchorhynchus mykiss	
	Acute crustacea toxicity	EC50	6100 mg/l	48 h	Daphnia magna	
78-93-3	butanone; ethyl methyl ketone					
	Acute fish toxicity	LC50	3220 mg/l	96 h	Pimephales promelas (fathead minnow)	GESTIS
	Acute crustacea toxicity	EC50	>100 mg/l	48 h	Daphnia magna (Big water flea)	
141-78-6	ethyl acetate					
	Acute fish toxicity	LC50	>100 mg/l	96 h	Salmo trutta fario (L) (Freshwater trout)	OECD 203
	Acute algae toxicity	ErC50	>100 mg/l	72 h	Desmodesmus subspicatus.	
	Acute crustacea toxicity	EC50	>100 mg/l	48 h	Daphnia magna (Big water flea)	

#### 12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
78-93-3	butanone; ethyl methyl ketone			
		98%	28	
	Readily biodegradable (according to OECD criteria).			
141-78-6	ethyl acetate			
	OECD 301D/ EEC 92/69/V, C.4-E	>70%	28	

#### 12.3. Bioaccumulative potential

The product has not been tested.

##### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-64-1	acetone; propan-2-one; propanone	-0,24
78-93-3	butanone; ethyl methyl ketone	<=4
141-78-6	ethyl acetate	0,68

#### 12.4. Mobility in soil

The product has not been tested.

#### 12.5. Results of PBT and vPvB assessment

Not identified as PBT/ vPvB substances

#### 12.6. Other adverse effects

No information available.

#### Further information

Avoid release to the environment.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### sili spray Adhesive

Print date: 26.10.2015

Product code: 10105\_1

Page 8 of 9

#### Advice on disposal

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

#### Contaminated packaging

Completely emptied packages can be recycled.

### SECTION 14: Transport information

#### Land transport (ADR/RID)

<b>14.1. UN number:</b>	UN 1950
<b>14.2. UN proper shipping name:</b>	AEROSOLS
<b>14.3. Transport hazard class(es):</b>	2
<b>14.4. Packing group:</b>	-
Hazard label:	2.1
Classification code:	5F
Limited quantity:	1 L/ 30 kg
Transport category:	2
Tunnel restriction code:	D

#### Other applicable information (land transport)

Flammable gas

#### Marine transport (IMDG)

<b>14.1. UN number:</b>	UN 1950
<b>14.2. UN proper shipping name:</b>	AEROSOLS
<b>14.3. Transport hazard class(es):</b>	2.1
<b>14.4. Packing group:</b>	-
Hazard label:	2.1
Marine pollutant:	-
Limited quantity:	1000 mL/ 30 kg
EmS:	F-D, S-U

#### Other applicable information (marine transport)

Flash point: &lt;-10°C c.c.

#### Air transport (ICAO)

<b>14.1. UN number:</b>	UN 1950
<b>14.2. UN proper shipping name:</b>	AEROSOLS, flammable
<b>14.3. Transport hazard class(es):</b>	2.1
<b>14.4. Packing group:</b>	-
Hazard label:	2.1
Limited quantity Passenger:	30 kg G
Passenger LQ:	Y203
Excepted quantity:	E0
IATA-packing instructions - Passenger:	203
IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

#### Other applicable information (air transport)

Flammable gas

#### 14.6. Special precautions for user

Warning: Flammable gases.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### sili spray Adhesive

Print date: 26.10.2015

Product code: 10105\_1

Page 9 of 9

#### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

not applicable

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

2010/75/EU (VOC): 84,867 % (577,096 g/l)

2004/42/EC (VOC): 84,867 % (577,096 g/l)

##### Additional information

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC, 2008/47/EC

##### National regulatory information

Employment restrictions: Observe employment restrictions for young people.

Water contaminating class (D): 1 - slightly water contaminating

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information

#### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

#### Relevant H- and EUH-phrases (Number and full text)

H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

#### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*